

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Temperature Transmitter

with type designation(s)
Transmitter Display

Issued to

Senmatic A/S
Søndersø, Denmark

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Location classes:

Temperature	A
Humidity	B
Vibration	B
EMC	A
Enclosure	B (IP65)

Issued at **Høvik** on **2021-05-10**

for **DNV**

This Certificate is valid until **2026-05-09**.

DNV local station: **Denmark CMC**

Approval Engineer: **Nils Jarem**

.....
Marta Alonso Pontes
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

Transmitter Display

The transmitter display consists of two independent circuits with a temperature sensor input on each.

- The first circuit shows the temperature on the display when enough light is available to drive the circuit.
- The second circuit is powered by external power and transmits temperature data.

Display part

Reading range	Multiple scalings 0°C to 300°C 0°C to 600°C 0°C to 750°C
Resolution	1 K
Accuracy	Class 1 in accordance with DIN EN 13190
Luminous intensity	≥ 40 lux
Measurement cycle	3 sec
Digital display type	4-digit, 7-segment display, height: 25.4 mm

Transmitter part

Linearity deviation	< 0.1 % Full scale
Loop voltage	24 ±2 V DC, reverse polarity protected *
Output signal	4 - 20 mA
Multiple scalings	0°C to 300°C 0°C to 600°C 0°C to 750°C
Maximum load	500 Ω
Sensor break signal	> 21 mA
Short circuit signal	< 3.6 mA

*15 V DC – 26 V DC with Load_{max} = 250 Ω

Approval conditions

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

Type Approval documentation

Title	Drw No	Rev
Transmitter display drawing	800-TD-CS	00/2020-06-10
transmitter-display_v13_10032021	Data sheet	1.3/2021-03-10
IP 65 test of Transmitter Display	2F010479	2020-04-03
Type approval test of PT 1000 sensor system	P19-0185	2020-03-30

Tests carried out

Applicable tests according to class guideline DNVGL-CG-0339, December 2019.

Marking of product

The products to be marked with:

- manufacturer name
- model name
- serial number
- power supply ratings

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE